

P.CONN.041
(MS 3116 F14 - 12P)

0.75mm² x 12 Core Black Cable

A.RS.080
A.RS.080
A.RS.080
A.RS.080
A.RS.080
A.RS.080

GROUP	12-PIN MILITARY CONNECTOR PIN	WIRE LABEL	WIRE COLOUR	DT06-2S WIRING ¹
RIGHT	A C D	VCC UP 2	RED	
		DOWN 2	BROWN AQUA	
LEFT	L G H	VCC UP 1	GREEN	
		DOWN 1	YELLOW ORANGE	
AUXILIARY 1	J E F	GND AUX 1 UP	WHITE	
		AUX 1 DOWN	PINK BLACK	
AUXILIARY 2	M B K	GND AUX 2 UP	PURPLE	
		AUX 2 DOWN	BLUE GREY	

¹ Order of wire pairs for each DT06-2S is not relevant.

Each pair
Ø6mm
Heat Shrink

Each Group
Ø13mm
Heat Shrink
Length=90mm

LEFT SIDE

500mm

UP

DOWN

UP

DOWN

RIGHT SIDE

AUX1 UP


DOWN

AUX2

UP

DOWN

8 x DT06-2S
(P.CONN.059)
Crimps: 04 62-201-16141
Wedge Lock: W2S



FRONT VIEW

DUO2.CAN Menu Selection:

- 1) Hydraulic Type: I[O] or On/Off Low Side
- 2) Auxiliary 2 = On or Joystick Type = Multi-Mode Side Mini if using joystick

RevNo	Revision note	Date	Signature	Checked	Tolerances	Path: MSD - 2-TECH - 2-TECH\Product Data\Cables\Electronic CAD\PDF Output\A.RS.080							
					Unless Stated:	Material:					Finish:		
					xx.x = +/- 0.1	Drawn by:	Checked by:	Unit:	aumoba Code:	Date:	Scale:		
					xx.xx = +/- 0.05	N.A.	C.R.	mm	A.RS.080	4/12/23	NTS		
					xx.xxx = +/- 0.02						Title: A.RS.080 with DT06-2S for I[O] or On/Off Low Side Main Hydraulics and 2 Auxiliaries		
											Drawing No:	Version:	Sheet: A3